

HIGHWAY Solar Module

HT60-156P-4BB-255W/260W/265W

Reliable State-owned Enterprise
Deliver Solar Power since 1960s






Shanghai Aerospace Automobile
Electromechanical Co., Ltd

Key Features

Cell Efficiency **18.2%** Power Output **265 W**

Warranty on Materials and Workmanship **10 YEARS**

Warranty on Power Output **25 YEARS**



Shorter current transmission path



Less SOLAR CELL'S series resistance



PID (potential induced degradation) Resistant



All HT modules are double EL tested avoiding invisible cracks, dark cells and broken bars to ensure the performance, quality and reliability.



Independent international authentication certified.



HT-SAAE guarantees highest production standards: IEC 61215, IEC 61730, IEC 62716 (Ammonia corrosion) & IEC 61701 (Salt Mist Corrosion)




Higher module's output power



Guaranteed positive tolerance 0/+5w ensures power output reliability



Excellent performance under low light environments (mornings, evenings and cloudy days)



All the modules are sorted and packaged by amperage, reducing mismatch losses and maximizing system output.



Entire module certified to withstand extreme wind (2400 Pa) and snow loads (5400 Pa)



Strict quality control, meeting the highest international standards: ISO 9001, ISO14001 and OHSAS18001



Electrical Characteristics

STC

Module	HT60-156P-4BB-255	HT60-156P-4BB-260	HT60-156P-4BB-265
Maximum Power at STC(Pmax)	255W	260W	265W
Open-Circuit Voltage(Voc)	37.4V	37.6V	37.8V
Optimum Operating Voltage (Vmp)	30.9V	31.3V	31.7V
Short-Circuit Current(Isc)	8.90A	8.97A	9.04A
Optimum Operating Current(Imp)	8.27A	8.32A	8.37A
Module Efficiency	15.7%	16.0%	16.3%
Power Tolerance	0 ~ +5W		
Maximum System Voltage	1000V DC (IEC) / 600V DC(UL)		
Maximum Series Fuse Rating	15A		
Operating Temperature	-40 °C to + 85 °C		

STC: Irradiance 1000W/m², module temperature 25, AM=1.5

Optional black frame or white frame module according to customer requirements

NOCT

Module	HT60-156P-4BB-255	HT60-156P-4BB-260	HT60-156P-4BB-265
Maximum Power	186W	190W	194W
Open Circuit Voltage (Voc)	33.8V	34.0V	34.2V
Maximum Power Voltage (Vmp)	27.9V	28.3V	28.7V
Short Circuit Current (Isc)	7.19V	7.24A	7.30V
Maximum Circuit Current (Imp)	6.68A	6.72A	6.76A
NOCT	45 °C ± 2 °C		

NOCT : Irradiance 800W/m², ambient temperature 20°C, wind speed 1 m/s

Mechanical Characteristics


Solar Cells	Polycrystalline 156 × 156mm	
No. of Cells	60 (6 × 10)	
Dimensions	1640 × 992 × 40/35mm (64.6 × 39.1 × 1.57/1.38in)	
Weight	19/18.5kg(41.9/40.8lbs)	
Front Glass	High transmission tempered glass	
Frame	Anodized aluminium alloy	
Junction Box	IP67 / IP65 3 diodes	
Cable	4mm ² (IEC) / 12AWG (UL), 900mm	
Connectors	MC4/MC4 Comparable	
Module Pieces per Container (40' High Cube Container)	700/784pcs (Varies depending on the size)	

Temperature Characteristics



Temperature Coefficient of Pmax	γ (Pm)	-0.41%/K
Temperature Coefficient of Voc	β (Voc)	-0.34%/K
Temperature Coefficient of Isc	α (Isc)	0.049%/K

Warranty

- 10-year product warranty
- 25-year warranty on power output
- Specific information is referred to the product quality guarantee



I-V Curves



* Copyright@1504A Specifications are subject to change without further notification